

Serial No.: 10/079,027
Conf. No.: 6406

- 2 -

Art Unit: 3673
Reply to August 11, 2006 Action

In the Claims:

Please replace all prior versions of claims in the application with the following claims.

1. (Currently Amended) A sealing device for providing a seal in vacuum applications for processing systems comprising:

a shaft that substantially extends longitudinally along an axis that is collinear with a central axis of a port between a first zone and a second zone[[s]] having a pressure differential existing therebetween, where the shaft may be positioned at a range of angles with respect to the central axis of the port for enabling movement of a device in the second zone by an external controller in the first zone;

a shaft seal having a sealing portion and a support portion, the sealing portion being disposed on the shaft to maintain a vacuum seal about the shaft, the sealing portion constructed and arranged to ~~sealingly engage with a shaft and~~ allow the shaft to be at least one of slidingly and rotationally moved by the external controller relative to the sealing portion in two or more degrees of freedom to achieve the range of angles to the port; and

a seal mount having a first end, a second end and a flexible member between the first and second ends that enables movement of the first end relative to the second end in at least one degree of freedom, the first end being sealingly engageable to at least a portion of the support portion of the shaft seal, the second end being sealingly engageable to an engagement surface about the port into a vacuum process chamber to maintain a vacuum seal for preventing contamination of the vacuum process chamber.

2. (Previously Presented) The sealing device of claim 1, wherein the flexible member defines a transition space in the first zone, the transition space being in fluid communication with the vacuum process chamber.

3. (Previously Presented) The sealing device of claim 1, wherein the flexible member allowing movement of the shaft seal in at least two degrees of freedom relative to the central axis of the port.

Serial No.: 10/079,027

- 3 -

Art Unit: 3673

Conf. No.: 6406

Reply to August 11, 2006 Action

4. (Original) The sealing device of claim 1, wherein the port further comprises a port size and a portion of the shaft extending through the port has a shaft size, the port size being substantially larger than the shaft size.

5. (Previously Presented) The sealing device of claim 1, wherein the port comprises a central axis, and the shaft seal is movable to allow the shaft to be angularly offset relative to the central axis of the port.

6. (Previously Presented) The sealing device of claim 1, wherein the shaft seal is movable to allow the shaft to be laterally offset relative to the central axis of the port.

7. (Original) The sealing device of claim 1, wherein the sealing portion of the shaft seal sealingly engages with a cylindrically-shaped portion of the shaft.

8. (Cancelled)

9. (Original) The sealing device of claim 1, wherein the sealing portion sealingly engages the shaft so that the shaft may be rotationally moved, but not slidingly moved, relative to the sealing portion.

10. (Original) The sealing device of claim 1, wherein the support portion includes a housing having a shaft bore with an inner surface, the shaft bore constructed and arranged to allow the shaft to pass through the shaft bore.

11. (Original) The sealing device of claim 1, wherein the support portion of the shaft seal is characterized as being substantially rigid.

12. (Original) The sealing device of claim 11, wherein the shaft seal includes a portion constructed from at least one member of the group consisting of metals, powder metals, ceramics, metallo-ceramics, rigid plastics, and combinations thereof.

Serial No.: 10/079,027
Conf. No.: 6406

- 4 -

Art Unit: 3673
Reply to August 11, 2006 Action

13. (Original) The sealing device of claim 1, wherein the flexible member includes at least one of natural rubber, silicone rubber, and elastomeric polymer materials.

14. (Currently Amended) The sealing device of claim 1, wherein the flexible member includes ~~at least one of natural rubber, silicone rubber, and elastomeric polymer materials~~ a plurality of undulations.

15. (Original) The sealing device of claim 1, wherein the flexible member includes a bellows portion.

16. (Original) The sealing device of claim 1, further comprising a first retaining ring constructed and arranged to sealingly engage a first end of the flexible member to the shaft seal.

17. (Original) The sealing device of claim 16, further comprising a first O-ring positioned between the first retaining ring and the shaft seal.

18. (Previously Presented) The sealing device of claim 1, further comprising a second retaining ring constructed and arranged to sealingly engage a second end of the flexible member to an engagement surface of the vacuum process chamber.

19. (Original) The sealing device of claim 18, further comprising a second O-ring positioned between the second retaining ring and the engagement surface.

20. (Original) The sealing device of claim 1, wherein the flexible member includes a flexible collar.

21. (Original) The sealing device of claim 20, wherein the shaft is moveable in a reciprocating manner relative to the shaft seal and the port.

22. (Original) The sealing device of claim 20, wherein the shaft is moveable in a rotating manner relative to the shaft seal and the port.

Serial No.: 10/079,027
Conf. No.: 6406

- 5 -

Art Unit: 3673
Reply to August 11, 2006 Action

23. (Original) The sealing device of claim 1, wherein the sealing member comprises:
a first seal member, a second seal member, and a spacer member positioned
therebetween, each of the seal members having a first surface and a second surface, the first
surface being supported by the support portion and the second surface being sealingly associated
with the shaft.

24. (Original) The sealing device of claim 23, further comprising a differential space
between the first and second seal members, the differential space being fluidly connectable with
a vacuum source.

25. (Original) The sealing device of claim 24, wherein the differential space is located
between the spacer seal member and the support portion.

26. (Original) The sealing device of claim 25, wherein the seal mount defines a
transition space in the first zone, and the differential space is fluidly connectable to transition
space.

27. (Currently Amended) A floating shaft seal for providing a vacuum seal for
processing systems comprising:

a reciprocating and ~~[[/]]~~ rotating shaft, wherein the shaft substantially extends
longitudinally along an axis that is collinear with a central axis of a port and is passed from a
zone at ambient air pressure through an opening in a vacuum process chamber, the vacuum
process chamber having a substantially lower pressure than ambient, where the shaft may be
positioned at a range of angles with respect to the central axis of the port for enabling movement
of a device in the vacuum ~~implantation~~ process chamber by an external controller from the zone
at ambient air pressure;

a sealing member constructed and arranged to ~~sealingly engage with a shaft and allow the~~
shaft to move responsive to the external controller relative to at least a portion of the sealing
member in two or more degrees of freedom to achieve the range of angles in the port, ~~the sealing~~
~~member being disposed on the shaft to maintain a vacuum seal about the shaft;~~ and

Serial No.: 10/079,027
Conf. No.: 6406

- 6 -

Art Unit: 3673
Reply to August 11, 2006 Action

a flexible mounting collar having a first end opening and a second end opening, the first end opening being sealingly engageable with the sealing member, the second end opening sealingly engageable about the opening in the vacuum process chamber to maintain the vacuum seal for preventing contamination of the vacuum process chamber.

28. (Previously Presented) The shaft seal of claim 27, wherein the opening in the vacuum process chamber has a central axis, and the sealing member and the flexible mounting collar are constructed and arranged to allow the shaft to be offset relative to the central axis.

29. (Original) The shaft seal of claim 28, wherein the sealing member and the flexible mounting collar are constructed and arranged to allow the shaft to be rotated about an axis transverse to the central axis.

30. (Original) The shaft seal of claim 27, wherein the sealing member is constructed and arranged to allow the shaft to rotate relative to at least a portion of the sealing member.

31. (Original) The shaft seal of claim 27, wherein the sealing member is constructed and arranged to allow the shaft to slide along a longitudinal axis of the shaft relative to at least a portion of the sealing member.

32. (Currently Amended) The shaft seal of claim 27, wherein a portion of the sealing member sealingly engages with is disposed on a cylindrical portion of the shaft.

33. (Currently Amended) A device for maintaining a seal for processing systems comprising:

a mobile shaft that substantially extends along an axis that is collinear with a central axis of a port from a first chamber into a second vacuum process chamber, the first chamber having a first pressure, the second process chamber having a second pressure, where the shaft may be positioned at a range of angles with respect to the central axis of the port for enabling movement of a device in the second vacuum process chamber by an external controller in the first chamber;
an inner housing having an inside surface and an outside surface, the inside surface

Serial No.: 10/079,027

- 7 -

Art Unit: 3673

Conf. No.: 6406

Reply to August 11, 2006 Action

defining a substantially cylindrical passage, a first portion of the substantially cylindrical passage having a first diameter sized to allow passage of the shaft therethrough;

an upper mechanical seal member, a lower mechanical seal member, and a spacer seal member positioned therebetween, each of the seal members having a first surface and a second surface, the first surface being supported by the first portion of the substantially cylindrical passage, the second surface being sealingly engaged with the shaft, at least one of the seal members being disposed on the shaft to maintain a vacuum seal about the shaft; and

an outer housing comprising a flexible member and having a first end and a second end, the first end sealingly engaged to a portion of the outside surface of the inner housing, the second end sealingly engaged to a wall of the second vacuum process chamber, the outer housing flexibly supporting the inner housing so that inner housing is moveable by the external controller relative to the wall of the second vacuum process chamber in two or more degrees of freedom while maintaining a vacuum seal for preventing contamination of the second vacuum process chamber.

34. (Original) The device of claim 33, further comprising:

a differential space between the first surface of the spacer seal member and the first portion of the substantially cylindrical passage; and

a differential pumping line in fluid communication with the differential space, the differential pumping line extending from the differential space through the inner housing.

35. (Withdrawn) An ion beam measuring device comprising:

a vacuum chamber having an inside and an outside, the vacuum chamber being defined by a plurality of walls and housing an ion beam projected from a beam source, one of the plurality of walls having an opening;

a shaft having a first end and a second end, the shaft passing through the opening in one of the plurality of walls in the vacuum chamber;

a measuring device operatively engaged to the first end of the shaft;

a control unit positioned on the outside of the vacuum chamber and engaged with the second end of the shaft; and

a seal device mounted adjacently to a wall of the vacuum chamber, the seal device having

Serial No.: 10/079,027
Conf. No.: 6406

- 8 -

Art Unit: 3673
Reply to August 11, 2006 Action

a flexible member and sealingly engaging the shaft so the shaft is free to at least one of rotate and slide relative to the seal device, the seal device being sealingly engaged about the opening in one of the plurality of walls and resisting fluid flow from outside the vacuum chamber through the opening in one of the plurality of walls, the flexible member allowing the shaft to be offset relative to the opening in one of the plurality of walls while sealing engagement is substantially maintained with the shaft.

36. (Previously Presented) The sealing device of claim 1, wherein the processing systems comprise an ion implantation processing system.

37. (Previously Presented) The shaft seal of claim 27, wherein the processing systems comprise an ion implantation processing system.

38. (Previously Presented) The sealing device of claim 33, wherein the processing systems comprise an ion implantation processing system.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.